298-53 BICKLEY 3 LT LINEAR PENDANT INSTALLATION INSTRUCTIONS

CORBETT® LIGHTING

⚠ WARNING

DISCONNECT POWER BEFORE RE-LAMPING OR WIRING THE FIXTURE
READ ALL INSTRUCTIONS COMPLETELY BEFORE STARTING INSTALLATION.

⚠ CAUTION

TO AVOID THE RISK OF FIRE OR SHOCK, FIXTURE MUST BE INSTALLED IN COMPLIANCE WITH ALL APPLICABLE NATIONAL AND LOCAL ELECTRICAL/BUILDING CODES.

INSTALLATION AND MAINTENANCE OF THIS UNIT REQUIRES AN ELECTRICIAN OR CERTIFIED FACTORY TRAINED TECHNICIAN.

If an existing fixture is being replaced, remove it and note to which of the wires in the outlet box the fixture was attached. DO NOT SEPARATE ANY OTHER WIRES THAT MAY BE IN THE BOX. DO NOT DAMAGE THE INSULATION OF OLDER WIRING. In regular circumstances the BLACK wire will be the "Hot" lead and the WHITE wire will be the "Neutral" or "Common" lead

A GREEN or BARE COPPER wire is the "Ground". In older buildings it is always good practice to reconfirm the polarity of the wiring .

NOTICE

- **The important safeguards and instructions outlined on this sheet cannot cover all possible conditions and situations that may occur. it must be understood that common sense, caution and care factors that cannot be built into any product. Caution and care must be supplied by the person(s) installing, operating and caring of this lighting fixture.**
- **This fixture is designed to be mounted on a correctly installed standard round or octagon box or a through wiring box with a plaster frame. The box must be securely mounted to the structure of the building. The crossbar and hardware supplied should be used. directly mounting the fixture to the outlet box may make it impossible to correctly align the fixture.**
- **This fixture is supplied with a 16ft. aircraft cable . This feature allows the fixture to be mounted up to 14ft. in height.**

NOTICE:

CALIFORNIA PROP 65: THIS LIGHTING FIXTURE CONTAINS CHEMICALS KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER, BIRTH DEFECTS, AND/OR OTHER REPRODUCTIVE HARM. WASH HANDS AFTER USE.

FIXTURE PREPARATION

1. Remove the fixture, parts and parts bag(s) from the carton.

NOTICE:
Before discarding the carton, double check to make certain that all parts are found.



FIGURE-01

FIXTURE INSTALLATION

1. Attach the mounting strap to the junction box.
   (The green screw should face the floor)
   Place the mounting strap at the junction box
   and fasten using the round head screw.
   Adjust the nipple so they extend 3/16" beyond the canopy .

2. Insert the 3 cable wire organizer to the leadwire and to the adjacent aircraft cable. (See Figure -02)



FIGURE-02



FIGURE-03

3. Insert the aircraft cables on the cable gripper attached on the canopy. (See Figure -03)
4. Insert the lead wire on the coupling attached on the canopy. (See Figure -03)
5. Fasten the ground wire to the green or bare copper wire in the outlet box or the green screw on the mounting plate.

WARNING

Never fasten the ground wire to the black or "hot" wire! Failure to follow this instruction could result in serious injury or death!

6. Fasten the white fixture lead to the white wire in the outlet box. Fasten the wires together with an approved fastener (wire nut). Starting about 1" below the fastener, tightly wrap the connection with electrical tape so that the connections seals the end of the fastener.

WARNING

Make sure that there is no exposed wire or strands that could cause a dangerous short circuit!



7. Attach the fixture to the nipple on the mounting strap and secure the canopy with the RS Cap (See Figure-04).
8. To level the fixture or change the drop height based on your desire height, push the tab down on the grip lock either pull or push the aircraft cable. Repeat this to all aircraft until the fixture is level and with the desired height.
9. Scatter the 3 cable organizer throughout the aircraft cable length. (See Figure-04) Then tighten the screw on the cable wire organizer to the aircraft cable to keep the leadwire straight.
10. Install the lamps. (G9 LED lamp)

NOTICE:
This fixture is rated for 6w G9 LED lamp.



FIGURE-04

WARNING

DO NOT EXCEED RECOMMENDED WATTAGE!

11. Loosen the threaded caps and place them on the corners. (See Figure -05)

12. Place the glass to the fixture, slide it through the lamp. (See Figure -06)

13. Tighten the threaded caps evenly on both side to the glass to keep it centered to the fixture. Do not over tighten to avoid breakage of glass diffuser. (See Figure -07)

NOTICE:
If the fixture is being installed in a room with hard floor (tile, wood, etc.), place a blanket or carpet below the fixture before installing glass.



FIGURE-05



FIGURE-06



FIGURE-07

14. Restore power to the circuit breaker or fuse box.