KICHLER.

CAUTION - RISK OF SHOCK - Disconnect Power at the main circuit breaker panel or main fuse box before starting and during the installation.

Pass fixture electrical wire and ground wire through desired amount of stems D & E and screw together using supplied 1)

threaded nipples into coupler on top of fixture.

Screw in two (2) canopy mounting screws into the mounting strap and connect mounting strap to outlet box.

Connect the two (2) loops, chain link with two (2) threaded

3)

nipples to the canopy using the lockwasher and hexnut supplied.

4) Route wires and ground wire through chain link and through canopy into the electrical box. Connect the D & E stems to the lower loop.


Grounding instructions: (See Illus. A or B)

On fixtures where mounting strap is provided with a hole and two raise dimples. Wrap ground wire from outlet box around green ground screw, and thread into

B) On fixtures where a cupped washer is provided. Put ground wire from outlet box under cupped washer and green ground screw and thread screw into hole in mounting strap.

If fixture is provided with ground wire. Connect fixture


ground wire to outlet box ground wire with wire connector, after following the above steps. Never connect ground wire to black or white power supply wires.




6) Make wire connections. Reference chart below for correct connections and wire accordingly.

Connect Black or Red Supply Wire to:	Connect White Supply Wire to:
Black	White
*Parallel cord (round & smooth)	*Parallel cord (square & ridged)
Clear, Brown, Gold or Black without tracer	Clear, Brown, Gold or Black with tracer
Insulated wire (other than green) with copper conductor	Insulated wire (other than green) with silver conductor


*Note: When parallel wires (SPT I & SPT II) are used. The neutral wire is square shaped or ridged and the other wire will be round in shape or smooth (see illus.)





- Use the (2) two ball knobs and two (2) lockwashers to secure canopy after wire connections are completed per below.
- 8) Install approved bulb (not included).



NIPPLE







Date Issued: 06/29/16 IS-43982-US