INSTALLATION INSTRUCTIONS

Item#3307-84 (New. 12/14/2015) READ AND SAVE THESE INSTRUCTIONS

WARNING! SHUT POWER OFF AT FUSE OR CIRCUIT BREAKER. AVERTISSEMENT! COUPER LE COURANT AU NIVEAU DES FUSIBLES OU DU DISJONCTEUR.

HANGING THE FIXTURE (Fig. 1)

- Shut off the power at the fuse box or circuit breaker. If necessary, remove old fixture, including mounting hardware.
- 2. Carefully remove the fixture from the carton and check that all parts are included as shown in the illustration.
- 3. Secure socket assembly (G) into the nipple (F) of fixture body (H).
- 4. Align cloth shade (K) with screw (E) by using cap nut (L).
- Attach the mounting plate (A) to the junction box with mounting screws (B) (Size: #8-32N*L0.5"). The side of the mounting plate with "GND" marked on it and two convex points must face out.

CONNECTING THE WIRES (Fig. 2)

6. At this point, connect the electrical wire as shown in figure 2, making sure that all wire connectors are secured. If your outlet has a ground wire (green or bare copper), connect the fixtures ground wire to it. Otherwise, connect the fixture ground wire directly to the circular strap using the green screw provided.

COMPLETING THE INSTALLATION (Fig. 1)

- 7. Install the light bulbs (not included) in accordance with fixture specifications. (DO NOT EXCEED THE MAXIMUM WATTAGE RATING!). (NE PAS DEPASSER LA PUISSANCE NOMINALE MAXIMALE!)
- 8. Thread the nipple (I) to socket assembly (G) and tighten it with hex nut (J).
- 9. Align canopy (D) over the mounting plate (A) and secure with screws (C).
- Align spacer (M) followed by glass shield (N) onto nipple (I) to adjust spacer (M) to make glass (N) flat with cloth shade (K) and secure with finial (O).

Your installation is now complete. Return power to the junction box and test the fixture.

Note: Illustration (Fig. 1) on this manual is for installation purposes only. It may or may not be identical to the fixture purchased.



